



SAFETY DATA SHEET
“NEW COAT HIGH TEMPERATURE PAINT”

SECTION 1 – PRODUCT IDENTIFICATION			
Product Name:	“NEW COAT HIGH TEMPERATURE PAINT”		
Distributor:	Rubbedin Pty Ltd		
Address:	Unit 1/43 Neumann Road Capalaba QLD 4157		
Regular Phone No:	(07) 3245 3255	FAX:	(07) 3245 2554
Emergency Phone No:	0405358685	Email:	info@rubbedin.com.au
Substance:	Mineral turpentine based paint.	Product Use:	High temperature paint
Product Code:	15-00		

SECTION 2 – HAZARDS IDENTIFICATION	
Classification of the substance or mixture	
SUSMP Poisons Schedule	This product is classified as a Scheduled 5 Poison according to the SUSMP
Dangerous Goods	This product is classified as Dangerous Goods according to the Australian Dangerous Goods (ADG) Code.
GHS Classification	Flammable Liquid – Category 3 Specific target organ toxicity (Single exposure) – Category 3 Skin sensitization – Category 1A
Label elements	
GHS label pictograms	Flame, Exclamation Mark
Signal word	WARNING
Hazard statement(s)	
	Flammable liquid and vapour. May be harmful if swallowed. May cause an allergic skin reaction. May cause drowsiness or dizziness. May cause respiratory irritation.
Precautionary statement(s): General	
	Keep out of reach of children.
Precautionary statement(s): Prevention	
	Read label before use. Keep away from heat, sparks, open flames, hot surfaces – No smoking. Keep container tightly closed. Ground container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator as required. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
Precautionary statement(s): Response	
	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Wash with plenty of soap and water. Call a POISON CENTRE or doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation occurs get medical attention. If medical advice is needed have product container or label on hand. In case of fire: Use alcohol resistant foam for extinction. Collect spillage.



SAFETY DATA SHEET

“NEW COAT HIGH TEMPERATURE PAINT”

Precautionary statement(s): Storage	
	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Precautionary statement(s): Disposal	
	Dispose of contents/container in accordance with local regulations.
Note	
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its concentrated form, as supplied. Good hygiene and housekeeping practices should be adhered to.

SECTION 3 – INGREDIENTS

Ingredients:	CAS Number:	Proportion:
Alkyd resin	Various	30 - 40
Mineral turpentine	64742-88-7	30 - 40
Methyl Ethyl Ketoxime	96-29-7	< 1
Aluminium Powder	7429-90-5	<1

NOTE: Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication “List of Designated Hazardous Substances” or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication “Approved Criteria for Classifying Hazardous Substances”, or have been found NOT to meet the criteria of a dangerous substance as defined in the GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) , 4th edition United Nations 2011. Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.

SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES

Scheduled Poisons	Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons. (Phone Australia 131126 or New Zealand 0800 764 766).
First Aid Facilities	Normal washroom facilities.
Skin contact	Wash skin with plenty of water. Remove contaminated clothing and wash before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness develops.
Eye contact	Immediately irrigate with water for at least 20 minutes. Eyelids to be held open. Seek medical advice (e.g. ophthalmologist) if any irritation persists.
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).
Inhalation	Remove victim to fresh air away from exposure - avoid becoming a casualty. Seek medical advice (e.g. doctor) if symptoms persist.
Advice to Doctor	Treat symptomatically. All treatments should be based on observed signs and symptoms of distress of the patient.
Aggravated Medical Conditions	Treat according to symptoms. Avoid gastric lavage (stomach pumping): risk of aspiration of product to the lungs with the potential to cause chemical pneumonitis.

SECTION 5 – FIRE FIGHTING MEASURES

Fire and Explosion Hazards	Fire: Flammable liquid. Product may form flammable/explosive vapour- air mixture during use. Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and other possibly toxic gases and vapours on burning.
Extinguishing Media	Alcohol resistant foam, carbon dioxide, foam, dry powder. Do not use water jet.
Fire Fighting	Full protective clothing and self-contained breathing apparatus. Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Dyke for later disposal. Use extinguishing agents for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.
Flash Point	31 °C



SAFETY DATA SHEET




“NEW COAT HIGH TEMPERATURE PAINT”

SECTION 6 – ACCIDENTAL RELEASE MEASURES	
Emergency Procedures	<p>HAZCHEM code : ●3YE</p> <p>●3 = alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.</p> <p>Y = Yes – risk of violent reaction, recommend breathing apparatus, contain.</p> <ul style="list-style-type: none"> ➤ Shut off engine and electrical equipment off. ➤ No smoking or naked lights within 50 metres. ➤ Move people from immediate area; keep upwind. ➤ Send messenger to notify fire brigade and police. ➤ Tell them location, material quantity, UN number and emergency contact. Indicate condition of vehicle and damage or injuries observed. ➤ Warn other traffic. <p>E = People should be warned to stay indoors with all doors and windows closed. Evacuation may need to be considered. Consult control, police and product expert.</p>
Occupational Release	<p>In case of spill, remove all sources of ignition, increase ventilation, evacuate all unnecessary personnel. Isolate hazard area and deny entry. Wear personal protection as indicated in section 8 below. Spilt material may result in a slip hazard and should be absorbed into dry, inert material (e.g. sand), which then can be put into appropriately labelled drums. The wasted material can be disposed of by incineration (Preferably high temperature), by an approved agent according to local conditions.</p>
SECTION 7 – HANDLING AND STORAGE	
Handling	<p>Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use.</p>
Storage	<p>Avoid all sources of ignition – (heat, sparks, static electricity, open flame). Use flameproof equipment and fittings to prevent flammability risk. Store in a well-ventilated area. Store in a cool, dry place and out of direct sunlight. Store away from incompatible substances i.e. strong oxidizing agents, acids or bases. Keep containers closed at all times – check regularly for leaks.</p>
SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION	
Exposure Limits	<p>National Occupational Exposure Limits, as published by Safe Work Australia:</p> <p>Time-weighted Average (TWA): None established for specific product.</p> <p>Exposure Limits of individual ingredients: Mineral Turpentine 90 ppm.</p> <p>Short Term Exposure Limit (STEL): None established for specific product.</p>
Engineering Controls	<p>Use only in a well-ventilated area. Ensure airflow, where this product is used, is directed away from the operators. Ensure ventilation is adequate to maintain air concentrations below exposure standards. If this is not possible, use appropriate personal protective equipment (meeting the requirements of AS/NZS 1715 and AS/NZS 1716).</p>
Personal Protective Equipment	<p>This product is classified as hazardous according to the criteria of Worksafe Australia. Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. Final choice of appropriate protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. The following protective equipment should be available.</p>



SAFETY DATA SHEET

“NEW COAT HIGH TEMPERATURE PAINT”

Eye Protection 	<p>The use of safety glasses with side shield protection, goggles or face shield is recommended to handle in quantity, cleaning up spills, decanting, etc. Contact lenses pose a special hazard ; soft lenses may absorb irritants and all lenses concentrate them.</p>
Skin Protection 	<p>Overalls, work boots and elbow length gloves are recommended for handling the concentrated product (as per AS/NZS 2161, or as recommended by supplier) to handle in quantity, cleaning up spills, decanting, etc.</p>
Protective Material Types	<p>Material suitable for detergent contact – Butyl rubber, Natural Latex, Neoprene, PVC, and Nitrile.</p>
Respirator 	<p>No respirator should be required under normal conditions of use in well-ventilated areas (outdoors) provided air concentrations are below exposure standards. If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices. If the exposure limit is exceeded briefly, a full facepiece respirator with an organic vapour cartridge may be worn. For short elevated exposures, eg, spillages:- Appropriate organic vapour cartridge respirator as per the requirements of AS/NZS 1715 and AS/NZS 1716 (Respiratory protective devices). For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. Exposure Limit by more than ten times, air supplied apparatus should be used.</p>

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Viscous liquid	Colour	Black
Odour	Hydrocarbon	Specific Gravity	1.2 – 1.4 @ 25 °C
Boiling Point	148 - 190 °C	Freezing Point	Approximately 0 °C
Vapour Pressure	0.429 kPa	Vapour Density	Not available
Flash Point	31 ^o c	Flammable Limits	LEL 0.6 - UEL 7.0%
Water Solubility	Not soluble	pH	Not available
Volatile Organic Compounds (VOC)	30 - 40 % v/v	Coefficient of Water/Oil Distribution	Not available
Viscosity	Not available	Odour Threshold	Not available
Evaporation Rate	Not available	Per Cent Volatile	30 - 40 % v/v

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability	Stable at normal temperatures and pressure.
Conditions to Avoid	Sources of heat and ignition, open flames
Incompatible Materials	Oxidising agents, minerals acids, halogenated organic compounds.
Hazardous Decomposition	Product can decompose on combustion to form Carbon Monoxide, Carbon Dioxide, and other possibly toxic gases and vapours.
Hazardous Reactions	None known.



SAFETY DATA SHEET
“NEW COAT HIGH TEMPERATURE PAINT”

SECTION 11 – TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS	
No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:	
Ingestion	
short term exposure	Harmful if swallowed. May cause irritation to the throat, mouth and digestive tract. Large doses may cause drowsiness and may lead to unconsciousness. Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.
long term exposure	No information available.
Skin contact	
short term exposure	Irritant, both by contact and vapour. Possible sensitizer. Prolonged exposure may result in dryness and cracking.
long term exposure	Prolonged and repeated skin contact with undiluted solutions may induce eczematoid dermatitis and sensitization.
Eye contact	
short term exposure	Irritant, both by contact and vapour.
long term exposure	No information available.
Inhalation	
short term exposure	Vapour is irritating to mucous membranes and respiratory tract. Can cause dizziness, headaches, nausea and may lead to unconsciousness. Prolonged exposure to vapour may cause damage to the central nervous system.
long term exposure	This product may contain traces of ethylbenzene and naphthalene derivatives. These products are classified as “possible human carcinogen (Group 2B)”.
Carcinogen Status	
SWA	No significant ingredient is classified as carcinogenic by SWA.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	No significant ingredient is classified as carcinogenic by IARC.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	Not expected to be a skin sensitizer.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	No information available.
STOT-repeated exposure	No information available.
Aspiration Hazard	Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.

SECTION 12 – ECOLOGICAL INFORMATION

Eco-toxicity Product (as sold)	None available for specific product.
Persistence and degradability	Individual components stated to be not readily biodegradable.
Bio accumulative potential	None available for specific product.
Mobility in soil	None available for specific product.
Other adverse effects	None available for specific product.
Environmental Protection	Expected to be toxic to aquatic organisms. Product not miscible with water. AS WITH ANY CHEMICAL PRODUCT, DO NOT DISCHARGE BULK QUANTITIES INTO DRAINS, WATERWAYS, SEWER OR ENVIRONMENT. Inform local authorities if this occurs.



SAFETY DATA SHEET

“NEW COAT HIGH TEMPERATURE PAINT”

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal	<p>The relevant local, regional and national regulations must be complied with. It is among the tasks of the polluter to assign the waste to waste codes specific to industrial sectors and processes according to the national authority. It is recommended that details be worked out with the waste disposal company responsible.</p> <p>The waste can be disposed of in a suitable incinerator or approved landfill site, provided that national/ local legislation is complied with.</p> <p>Containers may retain some product residues which may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.</p>
-----------------	--

SECTION 14 – TRANSPORT INFORMATION

Labels Required			
ADG	Classified as Dangerous Goods.		
IMDG Marine Pollutant	No		
Land Transport (ADG)			
UN Number	1263	ADG Classification	3
Shipping Name	PAINT	ADG Subsidiary Risk	None allocated
Hazchem Code	●3YE	Packing Group	III
Packaging Method	3.8.3	Special Provisions	SP187
Segregation	<p>Class 3 – Flammable liquid shall not be loaded in the same vehicle or packed in the same freight container with:</p> <ul style="list-style-type: none"> ➤ Class 1, Explosives ➤ Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk ➤ Class 2.3, Toxic Gases ➤ Class 4.2 Spontaneously Combustible Substances ➤ Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides ➤ Class 6 Toxic Substances (where the flammable liquid is nitromethane) ➤ Class 7 Radioactive Substances. <p>Foodstuff and foodstuff empties.</p>		

SECTION 15 – REGULATORY INFORMATION

GHS Classification	This material is classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
SUSMP	This product is classified as a Scheduled 5 Poison according to the SUSMP.
ADG Code	This product is classified as Dangerous Goods according to the Australian Dangerous Goods (ADG) Code.
AICS	All ingredients present on AICS.

SECTION 16 – OTHER INFORMATION

Issue Date	30th November 2016
Version Number	V 3.0
Abbreviations and acronyms	<p>ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.</p> <p>AICS: Australian Inventory of Chemical Substances.</p> <p>CAS Number: Chemical Abstracts Service Registry Number.</p> <p>GHS: Globally Harmonized System of Classification and Labelling of Chemicals</p>



SAFETY DATA SHEET “NEW COAT HIGH TEMPERATURE PAINT”

	<p>HAZCHEM: An emergency action code of numbers and letters which gives information to emergency services.</p> <p>HSIS: Hazardous Substances Information System</p> <p>IARC: International Agency for Research on Cancer.</p> <p>NOHSC: National Occupational Health and Safety Commission.</p> <p>NTP: National Toxicology Program (USA).</p> <p>SDS: Safety Data Sheet</p> <p>STEL: Short Term Exposure Limit.</p> <p>SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.</p> <p>TWA: Time Weighted Average.</p> <p>UN Number: United Nations Number.</p>
Literature references	<p>Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work Australia)</p> <p>GHS Hazardous Chemical Information List (Safe Work Australia)</p> <p>Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.</p> <p>Global Harmonized System of Classification and Labelling of Chemicals (GHS)</p> <p>“Australian Exposure Standards”. Safework Australia</p> <p>Australian Code For The Transport Of Dangerous Goods By Road And Rail</p> <p>Standard for the Uniform Scheduling of Medicines and Poisons</p> <p>Material Safety Data Sheets – individual raw materials – Suppliers</p> <p>HSIS – Hazardous Substance Information System – National Safe Work Australia Data Base.</p> <p>HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.</p>
<p>This SDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.</p> <p>The SDS is valid for five years from date of issue but may be withdrawn and revised at any time prior to that date. All information contained in the Data Sheet is as accurate as possible at the time of issue. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. No expressed or implied warranties nor any responsibility for damages resulting from use of the information are given other than those implied mandatory by Commonwealth, State or Territory Legislation. If this product is to be re-packaged by others, it will be necessary for a new SDS to be generated by the re-packer.</p>	
End of SDS	