

SECTION 1 – PRODUCT IDENTIFICATION				
Product Name:	"BLACK PATCH STOVE PUTTY"			
Distributor:	Rubbedin Pty Ltd			
Address:	Unit 1/43 Neumann Road Capalaba QLD 4157			
Regular Phone No:	(07) 3245 3255 FAX: (07) 3245 2554			
Emergency Phone No:	0405358685	Email:	info@rubbedin.com.au	
Substance:	Putty	Product Use:	High Temperature Black	
			Putty.	
Product Code:	30-00			

SECTION 2 - HAZADOS	SIDENTIFICATION	
SECTION 2 – HAZARDS IDENTIFICATION Classification of the substance or mixture		
SUSMP Poisons Schedule	This product is NOT classified as a Scheduled Poison according to the SUSMP	
Dangerous Goods	This product is NOT classified as Dangerous Goods according to the Australian Dangerous	
, Q	Goods Code	
GHS Classification	Eye Irritation – Category 2A	
	Skin Irritation – Category 2	
Label elements		
GHS label pictograms	Exclamation Mark	
Signal word	WARNING	
Hazard statement(s)		
	Causes skin irritation.	
	Causes serious eye irritation	
Precautionary statement(s):	General	
	Keep out of reach of children. In emergencies call 000	
Precautionary statement(s):	Prevention	
	Wash hands thoroughly after handling.	
	Wear protective gloves and eye / face protection	
Precautionary statement(s):	Response	
	IF ON SKIN: Wash with plenty of soap and water. Specific treatment (see section 4 of this	
	SDS). If skin irritation occurs: Get medical advice.	
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present	
Precautionary statement(s):	and easy to do	
,	Store in accordance with local regulatory requirements	
Precautionary statement(s):		
	Dispose of contents/container in accordance with local regulations	
Note		
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its	
	concentrated form, as supplied. Good hygiene and housekeeping practices should be adhered to.	

SECTION 3 – INGREDIENTS		
Ingredients:	CAS Number:	Proportion:
Silica Quartz Sand Cristobalite	14808-60-7 14464-46-1	60 - 90% w/w



FIRE WISE BLACK PATCH STOVE PUTTY

Ingredients determined to be non-hazardous at the concentrations used

Various

10 - 30% w/w

NOTE: Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from SWA publication "List of Designated Hazardous Substances" or have been found NOT to meet the criteria of a hazardous substance as defined in the SWA publication "Approved Criteria for Classifying Hazardous Substances", or have been found NOT to meet the criteria of a dangerous substance as defined in the GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS). Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.

SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES		
Scheduled Poisons	Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons. (Phone Australia 131126 or New Zealand 0800 764 766).	
First Aid Facilities	Normal washroom facilities.	
Skin contact	Wash skin with plenty of water. Remove contaminated clothing and wash before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness develops.	
Eye contact	Immediately irrigate with water for at least 20 minutes. Eyelids to be held open. Seek medical advice (e.g. ophthalmologist) if any irritation persists.	
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).	
Inhalation	Remove victim to fresh air away from exposure - avoid becoming a casualty. Seek medical advice (e.g. doctor) if symptoms persist.	
Advice to Doctor	Treat symptomatically. All treatments should be based on observed signs and symptoms of distress of the patient.	
Aggravated Medical Conditions	None known.	

SECTION 5 – FIRE FIGHTING MEASURES		
Fire and Explosion	Not combustible. However, if involved in a fire will emit toxic fumes.	
Hazards		
Extinguishing Media	Use an extinguishing media suitable for surrounding fires.	
Fire Fighting	Keep containers exposed to extreme heat cool with water spray. Fire fighters to wear self-	
	contained breathing apparatus if risk of exposure to products of combustion or	
	decomposition. Evacuate area - move upwind of fire.	
Flash Point	Not combustible.	

SECTION 6 – ACCIDENTAL RELEASE MEASURES		
Emergency Procedures	No HAZCHEM code.	
Occupational Release	Minor spills do not normally need any special clean-up measures. In the event of a major spill, prevent spillage from entering drains or water courses. For large spills, or tank rupture, consider initial evacuation distance of 200 metres in all directions. Stop leak if safe to do so. If available, use water spray to disperse vapour. Wear appropriate protective equipment as in section 8 below to prevent skin and eye contamination. Spilt material may result in a slip hazard and should be absorbed into dry, inert material (e.g. sand, earth or vermiculite), which then can be put into appropriately labelled drums for disposal by an approved agent according to local conditions. Residual deposits will remain slippery. Wash area down with excess water. If contamination of sewers or waterways has occurred advise the local emergency services. In the event of a large spillage notify the local environment protection authority or emergency services.	



SAFETY DATA SHEET FIRE WISE BLACK PATCH STOVE PUTTY

SECTION 7 – HANDLING AND STORAGE		
Handling	Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with water after handling.	
Storage	Store in a cool, dry, place with good ventilation. Avoid storing in aluminium and light alloy containers. Store away from incompatible materials (Section 10). Keep containers closed at all times – check regularly for leaks.	

SECTION 8 – EXPOSUR	E CONTROLS AND PERSONAL PROTECTION
Exposure Limits	National Occupational Exposure Limits, as published by Safe Work Australia: Time-weighted Average (TWA): None established for specific product. Short Term Exposure Limit (STEL): None established for specific product. Exposure Limits of individual ingredients: TWA Silica Quartz Sand (Respirable Dust) 0.1 mg/m3
Engineering Controls	No special requirements.
Personal Protective Equipment	Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. Final choice of appropriate protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. The following protective equipment should be available;
Eye Protection	The use of safety glasses with side shield protection, goggles or face shield is recommended to handle in quantity, cleaning up spills, decanting, etc. Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.
Skin Protection	Wear gloves to handle as per label directions. Overalls, work boots and elbow length gloves are recommended for handling the concentrated product (asper AS/NZS 2161, or as recommended by supplier) to handle in quantity, cleaning up spills, decanting, etc.
Protective Material Types	Material suitable for detergent contact – Butyl rubber, Natural Latex, Neoprene, PVC, and Nitrile.
Respirator	Not required for small use applications as per normal label applications. Consider a particle dust mask or respirator if dust hazard exists (eg sanding of dried putty).

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Putty	Colour	Black
Odour	Nil	Specific Gravity	Ca. 2.0 @ 25 °C
Boiling Point	Not available	Freezing Point	Not available
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	Not flammable	Flammable Limits	None
Water Solubility	Miscible in all proportions	рН	11.0 (initial in water)
Volatile Organic		Coefficient of Water/Oil	
Compounds (VOC)	0 % v/v	Distribution	Not available
Viscosity	Not available	Odour Threshold	Not available
Evaporation Rate	Not available	Per Cent Volatile	Ca 5 % v/v

SECTION 10 – STABILITY AND REACTIVITY	
Chemical Stability	Stable at normal temperatures and pressure.
Conditions to Avoid	None known.



Incompatible Materials	None known.
Hazardous	Product can decompose on combustion to form Carbon Monoxide, Carbon Dioxide, and
Decomposition	other possibly toxic gases and vapours.
Hazardous Reactions	None known.

SECTION 11 - TOXICO	DLOGICAL INFORMATION
POTENTIAL HEALTH EFFE	
	expected if the product is handled in accordance with this Safety Data Sheet and the product
	s that may arise if the product is mishandled and overexposure occurs are:
Ingestion	
short term exposure	Swallowing may result in a burning sensation in the mouth, throat, oesophagus and digestive system
long term exposure	No information available.
Skin contact	
short term exposure	This product is irritating to skin. Persons with pre-existing skin conditions may be sensitive to this product.
long term exposure	Prolonged and repeated skin contact with undiluted solutions may induce eczematoid dermatitis.
Eye contact	
short term exposure	This product is irritating to the eyes.
long term exposure	No information available.
Inhalation	
short term exposure	Not a dust hazard in moist form as supplied. Not a dust hazard when set. Sanding or grinding of set dry putty will generate dust. This may be irritating to the respiratory system if inhaled as a generated dust. This product may cause nose and throat irritation, coughing and shortness of breath.
long term exposure	Repeated exposure by inhalation of dry dust may cause serious chronic effects. Silica products contain crystalline silica, and when using the dry product, a portion of this may become airborne as respirable dust. Repeated exposure to respirable crystalline silica dust may lead to silicosis, a serious lung disease. The onset of silicosis is usually slow and lung damage may occur even when no symptoms or sign of ill health have occurred. Silicosis can develop to a more serious degree even after exposures have ceased, and may lead to other diseases including heart disease and scleroderma. Development of silicosis may increase the risk of later development of lung cancer. The toxicity of crystalline silica is directly proportional to the ability of any particle to reach the lower respiratory tract. Quartz particles with an aerodynamic diameter below 10um are likely to be most harmful to humans, as they reach the lower respiratory tract and are less readily removed by the lungs. Increases in lung cancer have been attributed to the inhalation of crystalline silica in a number of industries, including: ore mining; quarrying and granite works; ceramics pottery, refractory brick and diatomaceous earth industries; and in foundry workers. The International Agency for Research on Cancer has classified crystalline silica as a Group 1 Carcinogen – Carcinogenic to Humans, based on sufficient evidence in humans and animals. Increasing in vitro and in vivo evidence suggests that lung carcinomas in rats are a result of marked and persistent inflammation and epithelial proliferation.
Carcinogen Status	
SWA	No significant ingredient is classified as carcinogenic by SWA.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	The International Agency for Research on Cancer has classified crystalline silica as a Group 1 Carcinogen – Carcinogenic to Humans, based on sufficient evidence in humans and animals.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.



SAFETY DATA SHEET FIRE WISE BLACK PATCH STOVE PUTTY

Skin Sensitisation	Not expected to be a skin sensitizer.	
Germ cell mutagenicity	Not considered to be a mutagenic hazard.	
Reproductive Toxicity	Not considered to be toxic to reproduction.	
STOT-single exposure	Not expected to cause toxicity to a specific target organ.	
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.	
Aspiration Hazard	Not expected to be an aspiration hazard.	

SECTION 12 – ECOLOGICAL INFORMATION		
Eco-toxicity	None available for specific product	
Product (as sold)		
Persistence and	Individual components have been specifically included in this product because they are	
degradability	known to be readily biodegradable and of low toxicity to fish and other aquatic organisms.	
Bio accumulative potential	None available for specific product.	
Mobility in soil	None available for specific product.	
Other adverse effects	None available for specific product.	
	Expected to be harmful to aquatic species. Product miscible in all proportions with water. As	
Environmental Protection	with any chemical product, do not discharge BULK quantities into drains, waterways, sewer	
	or environment. Inform local authorities if this occurs.	

SECTION 13 – DISPOSAL CONSIDERATIONS		
Disposal	To dispose of quantities of undiluted product, refer to State Land Waste Management	
	Authority. Transfer product residues to a labelled, sealed container for disposal or recovery.	
	Waste disposal must be by an accredited contractor. As with any chemical, do not put down	
	the drain in quantity	

SECTION 14 – TRANSPORT INFORMATION				
Labels Required				
ADG	Not classified as Dangerous Goods.			
IMDG Marine Pollutant	No			
HAZCHEM	None allocated			
Land Transport (ADG)				
UN Number	none allocated	ADG Classification	none allocated	
Shipping Name	none allocated	ADG Subsidiary Risk	none allocated	
Hazchem Code	none allocated	Packing Group	none allocated	
Packaging Method	none allocated	Special Provisions	none allocated	
Segregation	none allocated			

SECTION 15 – REGULATORY INFORMATION		
GHS Classification	This product is classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations,	
	Australia.	
SUSMP	This product is NOT classified as a Scheduled Poison according to the SUSMP	
ADG Code	This product is NOT classified as Dangerous Goods according to the Australian Dangerous	
	Goods (ADG) Code	
AICS	All ingredients present on AICS.	

SECTION 16 – OTHER INFORMATION	
Issue Date	5 November 2021
Version Number	V 3.0



SAFETY DATA SHEET FIRE WISE BLACK PATCH STOVE PUTTY

Abbreviations and acronyms

ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.

AICS: Australian Inventory of Chemical Substances.

CAS Number: Chemical Abstracts Service Registry Number.

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HAZCHEM: An emergency action code of numbers and letters which gives information to

emergency services.

HCIS: Hazardous Chemicals Information System **IARC:** International Agency for Research on Cancer.

NTP: National Toxicology Program (USA).

SDS: Safety Data Sheet **SWA**: Safe Work Australia **STEL**: Short Term Exposure Limit.

SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.

TWA: Time Weighted Average. **UN Number**: United Nations Number.

Literature references

Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work

Australia)

GHS Hazardous Chemical Information List (Safe Work Australia)

Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.

Global Harmonized System of Classification and Labelling of Chemicals (GHS)

"Australian Exposure Standards". Safework Australia

Australian Code For The Transport Of Dangerous Goods By Road And Rail

Standard for the Uniform Scheduling of Medicines and Poisons Safety Data Sheets – individual raw materials – Suppliers

HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.

This SDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.

The SDS is valid for five years from date of issue but may be withdrawn and revised at any time prior to that date. All information contained in the Data Sheet is as accurate as possible at the time of issue. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. No expressed or implied warranties nor any responsibility for damages resulting from use of the information are given other than those implied mandatory by Commonwealth, State or Territory Legislation. If this product is to be re-packaged by others, it will be necessary for a new SDS to be generated by the re-packer.

End of SDS